



Contactless Magnetic Suspension High Speed Centrifugal Fan For HVAC Systems

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Aipu
- Model Number: GF125
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Export Standard Packaging
- Payment Terms: T/T, L/C



Product Specification

- Typology: Centrifugal Fan
- Flow Range: 68-156m³/min
- Boost: 40-100kPa
- Bear: Autonomous Domestic Magnetic Bearings
- Efficiency: 77%
- Highlight: **suspension high speed centrifugal fan, contactless high speed centrifugal fan, contactless high speed centrifugal turbo blowers**



More Images



for more products please visit us on aipukqdl.com

Product Description

Contactless Magnetic Suspension High-Speed Centrifugal Fan for HVAC Systems

Product Description

Ultra-low noise level
Adoption of magnetic levitation technology and optimised flow field design
Noise level can be reduced to below 55dB(A).
Creates a comfortable and quiet indoor environment for users

Excellent dustproof performance
Special sealing design effectively prevents dust from entering.
Stable operation in dusty environments such as factories, subways, etc.
Significantly reduces the need for regular cleaning and maintenance

High temperature adaptability
Special thermal management system and material selection
Stable operation in high-temperature environments above 50°C.
Meet the needs of special occasions, such as computer rooms, heat source systems, etc.

Programmable control system
Built-in advanced PLC controller and human-machine interface.
Users can adjust the parameters according to the actual needs of programming
Supports networking and docking with building automation system.

Outstanding anti-vibration performance
Magnetic levitation design eliminates mechanical vibration sources
Optimised fan structure to withstand strong vibrations
Suitable for earthquake-prone, severe vibration occasions

Performance Features

Energy saving and high efficiency

High-speed permanent magnet motor and high-efficiency ternary flow impeller are directly coupled.
More than 30% energy-saving than traditional Roots fan.
More than 20% energy-saving than multi-stage centrifugal blower.
More than 10% energy-saving than single-stage high-speed centrifugal blower.

Low noise

Adopting self-balancing technology, the vibration amount of magnetic levitation bearing is one order of magnitude smaller than that of traditional bearing and no friction. At the same time to take the active damping design, stable operation, body vibration is very small, fan noise at 80dB (A) or so.

Maintenance-free

Integrated design, skid mounted structure, easy installation, one key start and stop. Daily operation, free of mechanical maintenance, only need to replace the filter.

Intelligent control

Adopting PLC+GPRS/3G/4G, it can monitor the running status of the fan in real time, and realise the intelligent regulation of wind volume, wind pressure, rotational speed, etc. as well as manual mode control. In case of failure, it can also be remotely repaired and debugged.

Magnetic Levitation Blower Series Selection

Product Series	GF 50	GF 75	GF 100	GF125	GF 150	GF175	GF 200	GF 250	GF 300	GF350	GF 400
Motor power (KW)	50	75	100	125	150	175	200	250	300	350	400
Boost (kPa)	Inlet flow rate (m³/min) 1atm 20°C										
40	55	86	110	156	168	208	219	270	323	425	443
50	50	74	100	132	149	185	198	247	297	375	396
60	43	64	85	113	127	158	169	210	253	320	356
70	37	55	74	99	111	140	148	184	222	280	312
80	33	49	65	86	97	120	129	160	193	240	271
90	28	44	57	75	84	105	112	139	167	210	235
100		40	52	68	77	96	102	127	153	190	215
110					71	88	95	118	142	175	199
120					66	82	88	110	132	165	185
130									124	152	165
150											148
sizes(mm)	1700×1500×1480		1850×1700×1780			2150×1750×1700			2370×2260×2080		

Weight (kg)	800	1000	1200	1350	1500	1800	2000	2500	2800	3200	3500
-------------	-----	------	------	------	------	------	------	------	------	------	------


When the use conditions of the blower and the above table does not match, the need for performance conversion, our company can be non-standard design according to user requirements to meet the specific needs of users of various working conditions.

core technology

Core Technology with independent intellectual property right-Magnetic Bearing design and control technology

With independent intellectual property rights of 5 degrees of freedom magnetic levitation bearing technology, can ensure that when the equipment is energised, the rotor system can be levitated by electromagnetic force. The controller ensures more than 10,000 times of signal acquisition per second and gives real-time correction signals synchronously to ensure the stable levitation of the high-speed rotor.

With redundant power supply system and protection bearings to achieve multiple protection, will not cause any damage due to sudden power failure or fault shutdown.



Yixing Aipu Air System Equipment Co., Ltd



13771572002



183426306@qq.com



aipukqdl.com

Yixing Yicheng Street Hardware Electromechanical City, Phase I, Block 5, District 3, 8071