



Variable Speed Modular Roots Vacuum Pump Price For Energy Conscious Facilities

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Aipu
- Model Number: RR
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Export Standard Packaging
- Payment Terms: T/T, L/C



Product Specification

- Flow Range: 0.45-452.4m³/min
- Material: HT250
- Models: RR
- Flow Rate: 0.45-452.4m³/min
- Vacuum Degree: -9.8kPa~-80kPa
- Highlight: modular roots vacuum pump price,
modular roots type vacuum pump,
variable speed roots type vacuum pump



for more products please visit us on aipukqdl.com

Product Description

High-Efficiency Roots Vacuum System for Energy-Conscious Facilities

Product Features

Product Overview

Designed for energy-conscious industrial and commercial facilities, this high-efficiency roots vacuum system delivers outstanding performance while minimizing power consumption and operating costs. Leveraging advanced roots-type vacuum pump technology combined with intelligent drive and control systems, this vacuum system provides users with an exceptional blend of productivity, efficiency, and sustainability - essential attributes for organizations focused on reducing their environmental impact and utility expenses.

Key Technical Features

Premium Efficiency Roots Vacuum Pump

Optimized aerodynamic design and impeller geometry maximize vacuum output

High-performance permanent magnet motor and variable frequency drive

Comprehensive control algorithms continuously optimize energy use

Advanced Variable-Speed Operation

Adjusts vacuum pump speed in response to changing system demand

Eliminates wasteful constant-speed operation and part-load inefficiencies

Dramatically reduces overall energy consumption and operating costs

Smart, Connected Controls

Real-time performance monitoring and predictive maintenance features

Remote access and cloud-based analytics enable continuous optimization

Modular, Scalable Architecture

Allows for right-sizing to match specific facility vacuum requirements

Seamless integration with building management and SCADA systems

Facilitates future expansion and upgrades as needs evolve

Key Advantages

Exceptional energy efficiency minimizes utility expenses and carbon footprint

Intelligent, variable-speed operation optimizes performance and saves power

Advanced controls and connectivity support continuous system optimization

Modular, scalable design ensures a perfect fit for diverse facility needs

Scope of application

It is suitable for sewage treatment industry, petrochemical industry, food and drug industry, textile industry, metallurgy industry, cement and construction materials industry, printing and dyeing industry and other industries.

Market Distribution

We have 42 offices throughout the country, in addition to Taiwan Province, 33 provinces in the country's administrative regions have a sound sales and service network. We can provide you with pre-sale, in-sale and after-sales service in a timely and convenient manner, understand your needs, and constantly improve the service and quality system while meeting the customized needs of customers.

High Performance Aerodynamic Design Methodology for Wide Service Conditions

By studying the influence of impeller and volute flow on efficiency and working stability, the R&D team proposed a flow control method and a pneumatic optimization design method to improve the performance of the main engine, which greatly improved the efficiency of the main engine.

Manufacturing & Equipment Base

has built laboratories, R&D buildings, processing workshops, etc., with internationally advanced and China leading high-precision processing equipment.




Examples of uses



■水泡浴 Foaming in Bath



■燃烧炉 Combustion a Fireplace



■电镀槽搅拌 Stirring in Plated Vessel




■公寓大楼的污水处理（曝气）
Waste water Aeration in Condominiums



■工厂废水和畜产废水处理（曝气）
Waste Water Aeration for Shop and Livestock Industries




■养鱼用 Fish Care



■冲洗 Back Washing



■粉体输送（水泥、饲料、小片状物）
Transport of Particles



■食品真空包装
Vacuum Pack for Foods

RR-V系列罗茨真空泵性能表 Performance Data of Series RR-V Rotary Vacuum Pump				各真空度下的吸入风量 Q_s (m ³ /min) 和所需的轴功率 La (kW) 及配套电机功率 Po (kW) Inlet Flow Q_s (m ³ /min), Shaft Power La (kW) And Motor Power Po (kW)																												电机功率 Motor Power P_o (kW)								
型号 type	口径 mm	转速 n r/min	理论流量 Theoretical Capacity Q_s (m ³ /min)	~0.10Pa						~1.0Pa						~10Pa						~0.10Pa						~1.0Pa						~10Pa						
				~0.10Pa			~1.0Pa			~10Pa			~0.10Pa			~1.0Pa			~10Pa			~0.10Pa			~1.0Pa			~10Pa			~0.10Pa			~1.0Pa			~10Pa			
				Q_s	La	P_o	Q_s	La	P_o	Q_s	La	P_o	Q_s	La	P_o	Q_s	La	P_o	Q_s	La	P_o	Q_s	La	P_o	Q_s	La	P_o	Q_s	La	P_o	Q_s		La	P_o	Q_s	La	P_o			
RR-V025	25	1150	1.07	1	0.6	1.1	0.82	0.7	1.1	0.78	0.6	1.1	0.62	0.55	1.1	0.51	1.1	1.5																		4				
		1450	1.36	1.41	0.7	1.1	1.23	0.85	1.1	1.17	1	1.5	1.04	1.2	1.5	0.92	1.4	2.2	0.81	1.55	2.2															4				
		1750	2.4	1.83	0.9	1.1	1.65	1	1.5	1.39	1.5	1.5	1.36	1.5	1.5	1.34	1.6	2.5	1.25	1.8	2.2	1.14	2	3												4				
		2000	2.74	2.17	0.9	1.5	1.99	1.15	1.5	1.95	1.4	2.2	1.8	1.6	2.2	1.68	1.8	2.2	1.57	2.05	3	1.88	2.3	3	1.94	2.5	3										2			
		2800	3.92	3.95	1.1	1.5	2.67	1.5	2.2	2.61	1.7	3.2	2.48	2	3	2.99	2.3	3	3.25	2.55	3	3.18	3.5	4	3.92	3.1	4										2			
RR-V035	35	1150	1.11	1.54	1.3	2.2	1.38	1.85	2.2	1.5	2	3	1.57	2.35	3	3.05	2.7	4	3.39	3.05	4	3.45	3.4	4	3.71	3.75	3.5	3.42	4.1	3.5	2							4		
		1450	2.29	1.99	0.8	1.1	1.39	1	1.5	1.99	1.5	1.5	0.99	1.4	2.5	0.92	1.6	2.7																		4				
		1750	2.99	2.99	1	1.5	1.79	1.25	1.5	1.69	1.5	2.2	1.69	1.75	2.2	1.55	2	3	1.76	2.4	4	1.98	2.9	4												4				
		2000	3.49	2.99	1.2	1.5	1.79	1.5	2.2	2.28	1.8	2.2	2.09	1.95	2.5	3	1.95	2.3	3	1.76	2.4	4	1.98	2.9	4	3.02	3.65	3.5								2				
		2800	3.99	3.19	1.5	2.2	2.89	1.65	2.2	2.78	2	3	3.58	2.35	3	2.42	2.7	4	2.58	3	4	2.18	3.5	4	3.02	3.65	3.5										2			
RR-V055	55	1150	4.95	4.18	1.7	3	3.88	2.1	3	3.77	2.5	3	3.58	2.9	3	3.41	3.3	4	3.57	3.75	3.5	3.17	4.5	3.5	3.61	4.6	3.5										2			
		1450	5.95	5.18	2	3	4.88	2.5	3	4.77	3	4	4.58	3.5	4	4.41	4	5.5	4.57	4.5	5.5	4.17	5	7.5	4.65	5.5	7.5									2				
		1750	4.95	3.18	1.5	2.2	2.93	1.7	3	2.98	2.1	3	2.41	2.45	3	2.18	2.8	4	1.95	2.15	4															4				
		2000	5.95	4.58	1.5	3	4.81	2.1	3	3.96	2.5	4	3.59	3.85	4	3.74	3.5	5.5	3.71	3.95	5.5	3.94	4.5	5.5											4					
		2800	6.95	5.55	2	3	5.19	2.51	4	4.89	3.1	4	4.76	3.7	5.5	4.45	4.5	5.5	4.22	4.65	7.5	4.65	5.5	7.5	3.98	5.95	7.5									4				
RR-V085	85	1150	7.9	6.5	2.5	3	6.15	3.95	4	6	3.6	5.5	5.71	4.25	5.5	5.68	4.9	5.5	5.15	5.5	7.5	5.49	6.5	7.5	5.65	6.75	11									4				
		1450	9.79	8.95	2.5	4	8.11	3.9	5.5	7.96	4.4	5.5	7.66	5.2	7.5	7.44	6	7.5	7.21	6.95	11	7.94	7.7	11	6.95	8.5	11	6.62	9.5	15	2					4				
		1750	6.33	4.96	1.6	3	4.47	2.35	4	4.5	2.9	4	3.98	3.4	5.5	3.7	3.9	3.5	3.45	4.4	7.5	5.23	4.9	7.5											4					
		2000	7.99	6.32	2.5	3	6.13	3.95	4	5.95	3.6	5.5	5.84	4.25	5.5	5.76	4.9	7.5	5.11	5.18	7.5	4.89	6.5	7.5	4.89	6.85	11									4				
		2800	9.64	8.17	3.7	4	7.78	5.5	5.5	7.45	4.9	5.5	7.25	5.1	7.5	7.01	5.9	7.5	6.76	6.75	11	6.14	7.9	11	6.24	8.2	11	5.75	9	11	4					4				
RR-V105	105	1150	11	9.33	3	4	8.24	3.9	5.5	8.99	4.9	7.5	8.45	5.7	7.5	8.79	6.8	11	8.14	7.55	11	7.82	8.5	11	7.62	9.5	15	11.5	16.5	15							4			
		1450	13.7	12.3	3.9	5.5	11.9	4.95	7.5	11.7	6.1	7.5	11.4	7.25	11	11.3	8.4	11	10.9	9.5	15	10.7	10.4	15	10.4	11.75	15	9.98	12.9	16.5						4				
		1750	7.74	6.18	2.5	4	5.67	3.95	4	5.49	3.6	5.5	5.85	4.2	5.5	4.74	4.9	7.5	4.47	5.5	7.5	4.19	6.2	7.5											4					
		2000	9.17	7.62	3	4	7.1	5.45	5.5	6.88	4.5	5.5	6.53	5.65	7.5	6.17	5.8	7.5	5.9	6.55	11	5.82	7.3	11	5.27	8.1	11									4				
		2800	11.5	10	3.5	5.5	9.5	6.4	5.5	9.28	5.9	7.5	8.9	6.25	7.5	8.57	7.2	11	8.3	8.15	11	8.02	9.5	11	7.67	10.1	15									4				
RR-V165	165	1150	13.9	12.4	4	5.5	11.9	11.5	7.5	11.7	8.5	7.5	11.3	8.45	11	11	8.6	11	10.7	9.3	11	10.4	10.9	15	10	12.1	15	9.7	13.2	18.5						4				
		1450	15.9	14.4	4.5	5.5	13.9	13.8	7.5	13.7	7.1	11	13.3	8.45	11	12	9.8	15	12.7	10.9	15	12.4	12.5	15	12	13.8	18.5	11.7	15.2	18.5						4				

注：1. 带※的转速采用联轴器传动，其余转速采用皮带传动

Note: 1. Direct drive is adopted for model marked with "※", Belt drive is adopted for others.

RR-V系列罗茨真空泵性能表 Performance Data of Series RR-V Rotary Vacuum Pump																															
		各真空度下的吸入风量Qs (m³/min) 和所需的轴功率La (kW) 及配套电机功率 (kW)																													
		~0.06Pa						~1.0Pa						~10.0Pa						~0.1Pa											
型号 Type	口径 mm	转速 r/min	理论流量 Theoretical Capacity q/m³	~0.06Pa						~1.0Pa						~10.0Pa						~0.1Pa						电机 功率 Motor Power			
				Qs		La		Po		Qs		La		Po		Qs		La		Po		Qs		La		Po					
				Qs		La		Po		Qs		La		Po		Qs		La		Po		Qs		La		Po					
RR-V120	120	9700	13.1	8.90	2.4	4	8.32	5.7	5.9	8.97	4.8	7.5	3.6	5.30	7.3	7.2	6.3	11	6.80	2.45	11	6.82	8.4	11	6.97	9.3	11		8		
		1130	13.2	11	3.3	9	10.4	6.4	5.5	10.1	5.5	7.5	9.03	6.6	11	9.23	7.7	11	8.80	8.8	11	8.93	9.9	15	9.14	11	15		8		
		14000	16.6	16.6	4.2	5.3	13.8	3.55	7.5	13.5	6.8	11	13	8.3	11	12.6	9.7	11	12.3	13.1	15	12	12.5	15	11.6	13.9	18.3	11.1	13.3	18.3	8
		1750	24.4	20	17.9	5	7.5	21.3	6.7	11	17	8	11	16.5	18.1	10	16.1	21.7	15	15.8	15.4	18.5	15.3	18.5	15	16.8	22	14.5	16.5	22	8
		2000	22.9	20.7	5.7	7.2	20.6	7.4	11	19.8	9.5	12	19.3	11.3	15	18.9	11.4	18.5	18.6	15.3	18.3	18.1	12.2	22	17.9	18.3	22	17.4	21.1	20	8
RR-V120	120	9700	13.5	11	3.3	5.3	10.2	6.30	7.5	9.97	5.7	7.5	9.24	6.8	11	8.90	7.9	11	8.22	9.00	11	7.42	10.2	15					8		
		1130	16	13.5	4	5.3	11.7	7.30	7.5	12.3	6.7	11	11.7	8	11	11.2	9.9	15	10.7	10.7	15	10.3	12	15	9.8	13.5	15			8	
		14000	20.2	17.7	5	5.3	16.9	6.7	7.5	16.5	8.4	11	15.9	10.1	15	15.4	11.7	15	14.9	13.5	15	14.5	15.2	18.5	14	16.9	18.3	13.3	18.6	22	8
		1750	24.4	21.9	5.9	7.5	21.8	7.95	11	21.4	10	15	20.8	12.1	18.5	20.3	14.1	18.5	19.8	16.1	18.1	19.4	19.1	22	18.2	20.2	30	17.5	22.5	30	8
		2000	27.9	25.4	6.8	11	24.8	8.15	11	24.2	11.8	15	23.8	13.8	18.5	23.1	18.1	18.5	22.8	18.4	22	22.2	20.7	30	21.7	23.1	30	21	23.4	20	8
RR-V120	120	9700	16.9	13.9	4.3	5.3	12.9	5.70	7.5	12.5	7.2	11	12.9	8.8	11	12.3	10	10	10.9	11.4	15	10.2	12.8	15					8		
		1130	20	17	5	7.5	18	6.7	11	15.6	8.4	11	15	10.1	15	14.1	11.8	12	13.9	13.4	18.5	13.3	15	18.5	17.9	16.9	22			8	
		14000	25.3	22.2	6.2	7.5	21.9	8.30	11	20.9	10.5	15	20.3	12.6	18.3	19.7	14.7	18.5	18.2	18.9	22	18.9	19	22	18	21.1	20	17.1	23.2	30	8
		1750	30.5	27.4	7.5	11	26.5	10.1	15	26.1	12.6	15	25.3	15.2	18.5	24.9	17.7	22	24.4	20.3	30	23.9	22.8	30	23.3	24.8	30	22.5	26	37	8
		2000	34.9	31.8	8.5	11	30.9	11.4	15	30.5	14.3	18.5	29.9	17.5	22	29.3	20.2	30	28.9	25.1	30	28.2	26	30	27.6	29	37	26.7	31.9	37	8
RR-V120	120	9700	30.8	17.2	5.2	7.5	18.1	8.90	11	18.8	8.7	11	14.9	10.5	15	14.2	12.2	15	13.5	14	18.5	12.9	15.7	18.5	15.1	17.5	22			8	
		1130	24.4	21.2	6	7.5	20	8.3	11	19.5	10.5	15	18.8	12.3	15	18.1	14.4	18.5	17.1	16.5	22	16.8	18.5	22	16	20.6	30	15	22.7	30	8
		14000	31.1	27.5	7.3	11	26.4	10	15	26.9	12.3	18.5	25.7	13.4	18.5	24.1	18	22	23.9	20.4	30	23.1	23.2	30	22.4	25.9	30	21.4	26.5	37	8
		1750	37.5	33.9	8	11	30.8	12.2	15	30.3	15.3	18.5	29.6	16.5	22	29.9	21.8	30	29.2	25.8	30	28.8	28	37	28.3	31.2	37	27.8	33.2	40	8
		2000	42.9	39.3	10.2	15	36.2	13.9	18.5	35.7	17.5	22	37	21.1	30	36.3	24.7	30	35.9	28.3	37	35	31.9	37	34.2	36.5	41	31.2	36.1	40	8
RR-V120	120	9700	17.1	14.1	4.5	5.3	13.1	6.1	7.5	12.8	7.5	11	12.2	8.7	11	11.7	10.2	11	11.7	11.6	15	10.7	13.1	15	10.3	14.8	18.5			8	
		1130	22.1	19.1	6	7.5	18.7	8	11	18.4	10	15	17.8	11.8	15	17.3	13.3	18.5	16.8	15.5	18.5	16.3	17.5	22	15.7	18.5	22	15.1	21	30	8
		14000	27.4	24.8	7.5	11	23.8	8.75	11	23.1	10	15	22.5	14.3	18.5	22	16.3	22	21.5	18.8	22	21	30	28.4	23.5	30	18.9	25.5	30	8	
		1750	29.2	26.3	8	11	25.3	10.3	15	25	12.5	15	24.4	15	18.5	22.9	17.5	22	22.4	20	22	22.4	22.5	30	22.3	23	30	21.8	27.5	37	8
		2000	31.8	28.8	8.5	11	27.4	11	15	27.3	13.5	18.5	26.7	16.3	18.5	26.2	19	22	26.7	21.8	30	25.3	24	30	24.4	26.8	30	23.1	28.5	37	8
RR-V120	120	9700	33.9	30.9	8.40	11	28.9	12.3	18.5	28.6	15	18.5	28	18	22	28.3	20.8	30	28	25.6	30	28	25.6	30	28	25.6	37	26.4	32.2	37	8
		1130	31.6	28.8	8.5	11	27.4	11	15	27.3	13.5	18.5	26.7	16.3	18.5	26.2	19	22	26.7	21.8	30	25.3	24	30	24.4	26.8	30	23.1	28.5	37	8
		14000	33.9	30.9	8.40	11	28.9	12.3	18.5	28.6	15	18.5	28	18	22	28.3	20.8	30	28	25.6	30	28	25.6	30	28	25.6	37	26.4	32.2	37	8
		1750	37.5	33.9	8	11	30.8	12.2	15	30.3	15.3	18.5	29.6	16.5	22	29.9	21.8	30	29.2	25.8	30	28.8	28	37	28.3	31.2	37	27.8	33.2	40	8
		2000	42.9	39.3	10.2	15	36.2	13.9	18.5	35.7	17.5	22	37	21.1	30	36.3	24.7	30	35.9	28.3	37	35	31.9	37	34.2	36.5	41	31.2	36.1	40	8

注：带*的转速采用联轴器驱动，其余转速采用皮带驱动。
Notes: Direct drive is adopted for motor coupled with "*". Belt drive is adopted for others.

注：带*的转速采用联轴器直接传动，其余转速采用皮带传动。 Notes: Direct drive is adopted for model marked with "*", belt drive is adopted for others.

RR-V系列罗茨真空泵性能表 Performance Data of Series RR-V Rotary Vacuum Pump																																		
各真空度下的吸入风量Qs (m³/min) 和所需的轴功率La (kW) 及配套电机功率 (kW)																																		
Inlet Flow Qs (m³/min), Shaft Power La (kW) And Motor Power Po (kW)																																		
型号 Type	口径 mm	转速 r/min	理论流量 Theoretical Capacity q/m³	各真空度下的吸入风量Qs (m³/min) 和所需的轴功率La (kW) 及配套电机功率 (kW)																								电机 功率 Motor Power						
				~0.06Pa						~1.0Pa						~10.0Pa						~0.1Pa							P					
				Qs		La		Po		Qs		La		Po		Qs		La		Po		Qs		La		Po								
				Qs	La	Po	Qs	La	Po	Qs	La	Po	Qs	La	Po	Qs	La	Po	Qs	La	Po	Qs	La	Po	Qs	La	Po							
RR-V150	150	9700	26.8	17.4	5.3	7.5	12.9	7.3	11	15.8	8.7	11	15.1	10.7	15	14.4	12.1	15	13.9	13.9	18.5	13.4	15.3	18.5	13.8	17.5	22			8				
		1130	27.6	25.2	7	11	22	9.35	11	22.4	11.5	15	21.9	14	18.5	21.2	16.5	18.5	20.2	18.8	22	20.2	21	30	19.6	23.5	30	18.5	25.5	30	8			
		1170	25.3	23.9	8.3	11	20.7	11.3	15	20.3	13.4	18.5	22.6	16.9	22	20.8	19.3	22	20.3	22.5	30	20.9	20	30	20.3	27.9	37	24.6	30.5	37	8			
		1200	25.6	23.2	8	11	21	12	15	20.6	15	18.5	20.9	18	22	20.2	21	30	20.7	24	30	20.2	27	30	27.6	30	37	26.9	33	37	8			
		1350	30.4	28	9	5	23.1	12.8	15	23.8	15.8	15	23.1	18.3	30	30	22.5	30	31.5	25.8	30	31	30	37	30.4	35.5	37	28.7	34.5	40	8			
RR-V150	150	14000	41.3	37.8	10.9	15	36.6	14.1	18.5	36.2	17.6	22	35.8	21.1	30	34.9	24.6	30	34.3	28.1	37	33.8	31.9	37	33.2	38.1	45	32.6	38.5	45	8			
		1750	26.7	22.2	6.8	11	21	9	11	18.6	11.2	15	18.6	13.4	15	18.9	11.5	18.5	18.1	17.8	22	17.5	19.9	22	16.7	22.2	30			8				
		1800	35.3	31	8	11	23.8	11.5	15	23.4	13.5	18.5	28.5	17.5	22	27.7	20.8	30	27	23.5	30	28.4	28.4	30	27.5	28.5	37	24.8	32.5	37	8			
		1170	42.9	38.9	10	11	37.2	13.8	18.5	36.7	17.5	22	35.8	21	30	35	24.5	30	34.5	28.5	37	33.7	32	37	32.9	38.5	45	32.2	39	45	8			
		1200	45.8	41.3	11	15	40.1	14.8	18.5	38.6	18.5	22	38.7	22.5	30	37.9	26.5	30	37.2	30.5	37	36.6	38	45	34.8	37.8	45	34.1	41.5	50	8			
RR-V150	150	15000	48.4	42	12	15	43.8	16	18.5	43.5	20.9	30	42.4	24.5	30	41.6	29.5	37	36.9	32.5	37	40.7	39.8	45	38.3	40.9	45	38.8	45.5	50	8			
		14000	35.1	30.7	12.9	18.5	17.6	18.1	22	37	22.4	30	38	25.2	31	37	34.6	30.8	40	40.1	38	42.5	44.7	50	42.5	49.8	55	40	48	55	8			
		1750	33.4	30	8	11	37.4	14	15	36.9	12.8	15	35.5	16.3	18.5	18.2	18.4	30	29.2	32	31	30	35.2	39.8	31	31.2	37.7	37	18.7	30.6	37	8		
		1800	44.4	40	10.5	15	38.8	14.5	18.5	41.7	17	22	38.3	21.8	30	38.2	25.5	30	38.2	28.5	37	32.5	39.3	45	37	42.2	46.5	45	39.8	48	50	8		
		1170	33.2	30.2	12.9	15	47.6	17	37	36.2	21.5	30	43.5	24	30	44.4	30.5	37	43.4	37	42.5	39.8	45	40.5	44	50	40	46.5	50	8				
RR-V200	200	1250	57.2	52.8	13.8	18.5	15.3	16.3	22	50.4	23	30	48.1	27.8	37	48	32.5	37	47	31.5	45	46.1	42	50	45	47	50	43.4	52	75	8			
		1300	61.8	57.4	14.5	18.5	15.8	16.8	20	55	25	30	53.7	30	37	52.6	35	45	51.6	40.5	45	50.7	45.5	55	49.6	48.9	75	48.2	56	75	8			
		14000	66.4	60	16.9	22	60.6	22.1	30	60.6	27.7	37	60.3	30	37	57.2	36	45	56.2	44	55	53.3	49.7	54.2	55	52.8	49.8	75	4		75	8		
		15000	68.9	63.9	8.7	15	63.1	21.3	18.5	63.1	26.3	22	63.3	18.9	30	63.9	22.2	30	63.9	24.7	37	56.9	54.7	57	57.2	55.4	57	56.9	59	75	8			
		1750	54.2	48.9	12	15	47.3	17.2	22	46.6	20	30	45.4	26.5	37	44.2	31	37	42.3	35.5	45	42.3	40	50	41.1	44.4	50	39.3	50	75	8			
RR-V300	300	1170	68.5	60.1	18	18.5	18.5	21.8	30	57.8	30	37	56.1	37	55.2	40	54.5	43	50	53.8	48	50	52.8	45.5	52	50.7	50	75			75	8		
		1250	70	64.6	16	22	63	21.9	30	62.5	25.5	37	61.1	33.3	37	60	39	45	50	49	45	50	48	51	50	47	50	55.2	60	75	4		75	8
		1300	75.5	70.1	17	22	68.5	23.5	30	67.8	30	45	66.6	36	45	65.5	42	50	64.5	48.5	50	53.8	50	75	62.2	61.5	75	60.7	68	75	8			
		14000	81.1	75.7	18.9	30	74.1	25.8	30	73.4	32.8	37	72.2	38.9	37	71.1	45.7	55	70.1	52.7	75	69.1	58.7	75	67.9	68.7	75	66.3	73.6	80	4		75	8
		15000	83.9	78.9	11.6	15	83.9	16	18.5	83.4	20.4	30	80.7	24.8	30	80.3	29.7	37	80.1	33.5	37	76.9	67.9	75	75.3	65.3	75	73.8	80.2	75	8			
RR-V300	300	14000	68.1	62.5	15	18.5	40.5	21	30	68.7	37	57	67.2	35.5	45	66.7	43	54	54.1	50	52	50	52	50	50	48	50	50	48	50	8		75	8
		1170	80.5	76.7	18	22	74.7	26	30	73.9	32	37	72.7	39	50	70.9	48	50	69.8	47	75	68.2	49	75	66.7	67	75	64	74	80	4		75	8

各真空度下的吸入流量 Q_v (m^3/min) 和所需轴功率 P_a (kW) 及配套电机功率 (kW)

注: 1、☐ 内性能点真空泵配中间轴皮带轮传动
2、带*的转速采用联轴器直联传动。其余转速采用皮带轮传动

Notes: 1. Belt drive with counter shaft should be adopted for pump whose performance points are enclosed by the "☐"
2. Direct drive is adopted for model marked with "*", Belt drive is adopted for others.

注: 1、☐ 内性能点真空泵配中间轴皮带轮传动
2、带*的转速采用联轴器直联传动。其余转速采用皮带轮传动

Notes: 1. Belt drive with counter shaft should be adopted for pump whose performance points are enclosed by the "☐"
2. Direct drive is adopted for model marked with "*", Belt drive is adopted for others.

[illegible]

注: 1. ☐ 内性驱动真空泵中间轴皮带传动
2. 带泵的转速采用联轴器直联传动, 其余转速采用皮带传动

Notes: 1. Belt drive with counter shaft should be adopted for pump whose performance points are enclosed by the "☐"
2. Direct drive is adopted for model marked with "*", Belt drive is adopted for others.

注: 1. ☐ 内性驱动真空泵中间轴皮带传动
2. 带泵的转速采用联轴器直联传动, 其余转速采用皮带传动

Notes: 1. Belt drive with counter shaft should be adopted for pump whose performance points are enclosed by the "☐"
2. Direct drive is adopted for model marked with "*", Belt drive is adopted for others.

各真空度下的吸入风量 Q_s (m^3/min) 和所需的轴功率 La (kW) 及配套电机功率 (kW)

注: 1. 湿式罗茨真空泵不宜输送水溶性、腐蚀性的气体。
2. 带轮的转速采用联轴器直联传动, 其余转速采用皮带轮传动

Notes: 1. Water dissoluble or corrosive gas should not be transferred by wet rotary vacuum pump.
2. Direct drive is adopted for model marked with "S", Belt drive is for others.

注: 1. 湿式罗茨真空泵不宜输送水溶性、腐蚀性的气体。
2. 带轮的转速采用联轴器直联传动, 其余转速采用皮带轮传动

Notes: 1. Water dissoluble or corrosive gas should not be transferred by wet rotary vacuum pump.
2. Direct drive is adopted for model marked with "S", Belt drive is for others.

RR-W系列罗茨真空泵性能表 Performance Data of Series RR-W Rotary Vacuum Pump

型号		口径 mm	转速 r/min	理论流量 Theoretical Capacity Q _s /m ³ /min	各真空度下的吸入流量Q _s (m ³ /min) 和所需的轴功率La (kW) 及配套电机功率 (kW)																								吸入流量 Suction Flow Q _s /m ³ /min	电机 功率 Motor Power P/kW				
					Inlet Flow Q _s (m ³ /min), Shaft Power La(kW) And Motor Power Po(kW)																													
					~13.3kPa				~20.0kPa				~26.7kPa				~33.3kPa				~40.0kPa				~46.7kPa						~53.3kPa			
					Q _s	La	Po	Q _s	La	Po	Q _s	La	Po	Q _s	La	Po	Q _s	La	Po	Q _s	La	Po	Q _s	La	Po	Q _s	La	Po			Q _s	La	Po	
RRD-125R	125	900R	11.12	18.1	6.17	6.4	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	8.8	6.4	7.3				
			11.12	18.1	6.17	6.4	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	8.8	6.4	7.3				
			11.12	18.1	6.17	6.4	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	8.8	6.4	7.3				
			11.12	18.1	6.17	6.4	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	8.8	6.4	7.3				
			11.12	18.1	6.17	6.4	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	9.7	6.4	7.3	8.8	6.4	7.3	8.8	6.4	7.3				
RRD-125R	125	1500R	16.65	25.6	8.9	7.3	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4			
			16.65	25.6	8.9	7.3	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4			
			16.65	25.6	8.9	7.3	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4			
			16.65	25.6	8.9	7.3	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4			
			16.65	25.6	8.9	7.3	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4	8.9	10.2	11	15.4			
RRD-125R	125	2000R	22.84	34.9	9.3	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7			
			22.84	34.9	9.3	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7			
			22.84	34.9	9.3	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7			
			22.84	34.9	9.3	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7			
			22.84	34.9	9.3	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7	11	25.3	13.7	16.5	11	21.7			
RRD-125R	125	2500R	29.03	44.2	9.8	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3			
			29.03	44.2	9.8	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3			
			29.03	44.2	9.8	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3			
			29.03	44.2	9.8	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3			
			29.03	44.2	9.8	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3	16.2	18.5	13	28.6	13.1	32	18.3			
RRD-150R	150	900R	15.11	20.2	8	11	20.2	11.5	12	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14			
			15.11	20.2	8	11	20.2	11.5	12	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14			
			15.11	20.2	8	11	20.2	11.5	12	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14			
			15.11	20.2	8	11	20.2	11.5	12	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14			
			15.11	20.2	8	11	20.2	11.5	12	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14			
RRD-150R	150	1500R	21.39	29.5	10.9	13	29.1	14.3	18.5	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8			
			21.39	29.5	10.9	13	29.1	14.3	18.5	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8			
			21.39	29.5	10.9	13	29.1	14.3	18.5	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8			
			21.39	29.5	10.9	13	29.1	14.3	18.5	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8			
			21.39	29.5	10.9	13	29.1	14.3	18.5	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8	17.8	22	20.8			
RRD-150R	150	2000R	27.51	39.3	13.1	14	38.8	17.5	22	38.3	21.3	30	24.7	26.7	30	34.1	29.8	37	33.3	34	37	33.3	34	37	33.3	34	37	33.3	34	37	33.3			
			27.51	39.3	13.1	14	38.8	17.5	22	38.3	21.3	30	24.7	26.7	30	34.1	29.8	37	33.3	34	37	33.3	34	37	33.3	34	37	33.3	34	37	33.3			
			27.51	39.3	13.1	14	38.8	17.5	22	38.3	21.3	30	24.7	26.7	30	34.1	29.8	37	33.3	34	37	33.3	34	37	33.3	34	37	33.3	34	37	33.3			
			27.51	39.3	13.1	14	38.8	17.5	22	38.3	21.3	30	24.7	26.7	30	34.1	29.8	37	33.3	34	37	33.3	34	37	33.3	34	37	33.3	34	37	33.3			
			27.51	39.3	13.1	14	38.8	17.5	22	38.3	21.3	30	24.7	26.7	30	34.1	29.8	37	33.3	34	37	33.3	34	37	33.3	34	37	33.3	34	37	33.3			
RRD-150R	150	2500R	35.84	51.2	15	18.5	30.9	19.8	30	40.6	24.5	30	40.1	29.3	37	39.5	34.1	40	35.4	38.7	39.6	40	35.4	38.7	39.6	40	35.4	38.7	39.6	40	35.4			
			35.84	51.2	15	18.5	30.9	19.8	30	40.6	24.5	30	40.1	29.3	37	39.5	34.1	40	35.4	38.7	39.6	40	35.4	38.7	39.6	40	35.4	38.7	39.6	40	35.4			
			35.84	51.2	15	18.5	30.9	19.8	30	40.6	24.5	30	40.1	29.3	37	39.5	34.1	40	35.4	38.7	39.6	40	35.4	38.7	39.6	40	35.4	38.7	39.6	40	35.4			
			35.84	51.2	15	18.5	30.9	19.8	30	40.6	24.5	30	40.1	29.3	37	39.5	34.1	40	35.4	38.7	39.6	40	35.4	38.7	39.6	40	35.4	38.7	39.6	40	35.4			
			35.84	51.2	15	18.5	30.9	19.8	30	40.6	24.5	30	40.1	29.3	37	39.5	34.1	40	35.4	38.7	39.6	40	35.4	38.7	39.6	40	35.4	38.7	39.6	40	35.4			
RRD-180R	180	900R	22.70	31.2	8	11	20.2	11.5	12	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14			
			22.70	31.2	8	11	20.2	11.5	12	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14			
			22.70	31.2	8	11	20.2	11.5	12	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14			
			22.70	31.2	8	11	20.2	11.5	12	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14			
			22.70	31.2	8	11	20.2	11.5	12	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14	16.5	14			
RRD-180R	180	1500R	28.26	37.7	11.8	13	27.2	14.8	18.5	20.8	18.1	22	24.5	21.4	30	29.8	34.0	30	24.9	27.8	37	23.9	31.1	37	30.1	34.1	37	30.1	34.1	37	30.1			
			28.26	37.7	11.8	13	27.2	14.8	18.5	20.8	18.1	22	24.5	21.4	30	29.8	34.0	30	24.9	27.8	37	23.9	31.1	37	30.1	34.1	37	30.1	34.1	37	30.1			
			28.																															

注：1. 湿式罗茨真空泵不宜输送水溶性、腐蚀性的气体。
2. Direct drive is adopted for model marked with "D", Belt drive is for others.
3. Belt drive with counter shaft should be adopted for pump whose performance points are enclosed by the " ".

RR-W系列罗茨真空泵性能表 Performance Data of Series RR-W Rotary Vacuum Pump

型号	口径 mm	转速 r/min	理论流量 Theoretical Capacity Q _s /m³/min	各真空度下的吸入流量Q _s (m³/min) 和所需的轴功率La (kW) 及配套电机功率 (kW)																								吸入流量 Suction Flow Q _s /m³/min	电机 功率 Motor Power P/kW
				Inlet Flow Q _s (m³/min), Shaft Power La(kW) And Motor Power Po																									
				~13.3kPa			~20.0kPa			~26.7kPa			~33.3kPa			~40.0kPa			~46.7kPa			~53.3kPa							
				Q _s	La	Po	Q _s	La	Po	Q _s	La	Po	Q _s	La	Po	Q _s	La	Po	Q _s	La	Po	Q _s	La	Po	Q _s	La	Po		
RRD-150R	150	900R	16.65	19	8	11	18.7	10.2	11	18.7	10.2	11	18.7	10.2	11	18.7	10.2	11	18.7	10.2	11	18.7	10.2	11	18.7	10.2	11		
		950R	27.64	25.9	10.6	13	25.5	13.6	18.5	13	25.5	13.6	18.5	13	25.5	13.6	18.5	13	25.5	13.6	18.5	13	25.5	13.6	18.5	13	25.5		
		1170	33.74	33.9	12.6	13	31.2	16.4	18.5	16.7	18.1	30	34.3	23.9	26	37.7	21.3	27	38.3	21.3	27	37.7	21.3	28.4	43	19	4		
		1290	35.92	35.9	13.3	13	33.5	17.3	22	35	21.3	30	32.9	23.7	30	31.9	18.2	27	38	23.1	27	28.3	37.1	43	19	4			
		1390	38.74	36.7	14.6	18.5	36.1	18.9	22	36.9	23.1	30	35.4	27.2	27	34.7	17.7	27	36.7	18	41	41.4	48.2	43	19	4			
RRD-150R	150	1600R	41.92	38.1	15.6	18.5	39	20	38.1	25.9	39	39	20	38.1	25.9	39	39	20	38.1	25.9	45	39.4	45	44	45	19	4		
		1800R	48.38	34.9	16.3	11	24.4	12.3	13	25.9	13.4	18.5	23.5	18.6	22	23.5	13.4	30	31.3	24.6	38	38.8	27.3	31	18	4			
		950R	35.54	33.9	12.6	13	33.1	16.6	18.5	16.8	18.6	22	36.6	30	35.9	18	38	32.4	27	28.5	36.5	43	19	6					
		1170	42.97	35.9	15.1	18.5	40.5	19.3	30	45	24.8	30	34.9	29.4	27	36.6	14.1	43	37.1	39.1	43	33.7	43.7	53	20	4			
		1290	45.90	43.9	16.2	18.5	43.3	21.9	30	45.9	26.5	30	42.3	31.3	27	41.5	16.4	43	40.3	41.7	52	38.8	46.7	53	20	4			
RRD-150R	150	1500R	46.96	47.2	17.2	22	47.1	22	39	45.4	28.5	37	44	34	41	41.2	28.2	43	44	44.9	32	42.3	36.4	73	20	4			
		1600R	53.13	31.2	19	22	36.8	24.9	30	36.3	30.8	27	49.1	26.7	41	48.9	41.4	53	47.7	46.4	73	46	54.3	73	19	4			
		1800R	52.97	36.9	11.3	13	38.4	13.1	18.5	28.9	19	22	29.1	22.6	36	28.1	26.3	30	28.8	29.9	37	34.4	33.6	44	19	4			
		950R	44.43	41.9	14.9	22	41.4	19.9	22	45.9	21.7	30	48.1	28.6	27	38.1	14.6	43	37.9	38.9	43	33.4	44.5	53	20	4			
		1170	53.59	51.1	19	22	36.6	23.9	30	36	29.8	37	49.3	35.7	41	48.5	41.7	53	47	47.6	55	44.6	54.6	73	20	4			
RRD-150R	200	1290	37.35	34.7	18.1	22	34.7	25.3	30	33.6	33.1	27	32.9	38.7	43	31.9	44.3	53	36.6	31	73	48.2	37.3	73	20	4			
		1390	43.93	38.3	20	22	36.8	26.7	39	35.2	31.3	43	47.1	39.9	43	36.5	45.3	53	46.7	31	73	51.8	37.3	73	20	4			
		1600R	66.41	63.9	22.3	30	63.4	28.2	37	62.9	36.6	46	62.1	63.7	61	61.1	36.7	73	38.9	57.7	73	57.4	63.9	73	19	4			
		1800R	68.38	38.1	13.9	18.5	37.4	16.7	23	36.7	13.9	30	36.2	27.8	27	36.7	13.7	31	33.2	36.6	49	36.6	41	53	19	4			
		950R	54.39	51.5	18	22	36.9	24	30	36.2	19	27	49.3	30	48	48.2	42.2	53	46.7	48.2	53	44.1	54.2	73	19	4			
RRD-150R	200	1170	65.59	67.7	21.3	30	62.1	26.9	37	63.4	36	43	66.5	43.5	53	54.4	36.8	73	57.9	30	73	53.3	65.2	73	20	4			
		1290	78.00	47.2	25.9	38	66.1	26.3	37	65.9	38.2	43	63.5	43.9	53	62.9	53.3	73	62.1	44.3	73	59.8	70	80	20	4			
		1390	75.30	52.7	25.6	30	72.1	32	37	71.4	41.5	43	70.3	50	73	69.4	56.3	79	67.9	46.7	73	65.1	73	80	20	4			
		1600R	81.29	38.4	27	37	77.9	36	42	77.1	41.2	50	76.2	54.7	73	73.1	63.4	73	73.4	72.2	86	71	81.2	86	70	20	4		
		1800R	38.1	18.4	11.2	22	47.8	23.1	30	46.8	18.9	27	45.1	36.7	43	48.4	46.1	43	62.3	46.2	58	38.2	52	73	19	4			
RRD-210R	250R	950R	68.18	63.6	27.7	38	64.9	36.3	37	63.9	38	41	62.9	43.6	53	63.6	53.1	73	59.8	41.1	73	56.3	68.6	73	19	4			
		1170	81.38	78.9	27	37	79.1	36.1	43	78.1	43.6	50	77.1	59.9	73	73.6	64.1	73	73.6	64.1	73	73.6	64.1	73	19	4			

各真空度下的吸入风量 Q_s (m^3/min)和所需的轴功率 L_n (kW)及配套电机功率 (kW)

注: 1、湿式罗茨真空泵不宜输送水溶性、腐蚀性的气体。
2、带*的转速采用联轴器直接传动, 其余转速采用皮带轮传动

Notes : 1. Water dissoluble or corrosive gas should not be transferred by wet rotary vacuum pump.
2. Direct drive is adopted for model marked with "*", Belt drive is for others.

各真空度下的吸入风量 Q_s (m^3/min) 和所需的轴功率 L_a (kW) 及配套电机功率 (kW)

Notes: 1. Wet rotary vacuum pump should not be transferred by wet rotary vacuum pump.
2. Direct drive is adopted for model marked with "B", Belt drive is for others.
3. Belt drive with counter shaft should be adopted for pump whose performance points are enclosed by the "B".