

Ultra Silent Air Suspension Blower New Design Concept Without Impellers Smart Airflow Control

Basic Information

Place of Origin: ChinaBrand Name: Aipu

Model Number: Air Suspension Blowers

Minimum Order Quantity:

• Price: Negotiable

Packaging Details: Export Standard Packaging

• Payment Terms: T/T, L/C



Product Specification

Flow Range: 5-500m³/min
 Boost: 5-120kPa
 Temperature: Up To 60°C
 Filtration Efficiency: Up To 85 Per Cent

• Highlight: silent air suspension blower,

silent suspension centrifugal blower, ultra silent air suspension blower



Ultra Silent Suspension Blower - A new design concept without impellers.

Product Description

Key Features:

Radical Design Innovation:

Abandons the traditional impeller-based design

Utilizes magnetic levitation technology for a completely new approach

Whisper-Quiet Operation:

Friction-free magnetic suspension results in noise levels as low as 25 dB

Provides an exceptionally quiet and soothing environment

Smart Airflow Control:

Integrated intelligent control system

Allows for adjustable airflow to suit various needs

Versatile Applicability:

Suitable for use in offices, homes, and other spaces

Lightweight and portable for easy placement

Plug-and-Play Convenience:

Simple setup, just plug it in and start enjoying clean, circulated air

No complicated installation required

Foll Bearing Technology

Foil bearing has physical contact between therotor and the bearing before starting, therelative movement of the rotor and the bearinggenerates air pressure when starting, when therotor rotates, the speed of the air around therotor can be converted into pressure energy, andthe air pressure makes the rotor float when therotor reaches a certain rotation speed and playsa lubricatingrole. Foil bearing technologyeffectively solves the problems of lowefficiency, short life, and the need forregularmaintenance and lubrication of the traditional mechanical support transmission system.



Air Suspension Bearing High Speed Centrifugal Blower Series Selection

								_							
Air Flow (m/min):1atm,20°C,65%RH, density=12kg/m3, Tolerance=+5%															
model	Out	Outlet pressure (bar)									Weight	Outlet calibre	Dimension (mm)		
number															
number	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1	1.2	kw	ka	PN1.0 MPa	oldor	width	height
	Inle	Inlet Flow(m³/min)									kg	FINI.U IVIFA	eidei	widtri	Height
ZGK15	24	17	14	13	10	/	/	/	/	15	300	-DN150	1300	800	1230
ZGK22	36	29	24	21	18	16	/	/	7	22	310				
ZGK30	49	39	33	28	25	22	/	/	/	30	330				
ZGK37	62	48	41	35	31	28	25	22	19	37	350				
ZGK45	78	62	51	45	31	34	32	28	23	45	550	DN200	1500	1100	1580
ZGK55	94	76	60	54	47	40	38	34	28	55	630				
ZGK75	124	95	76	69	63	55	49	45	37	75	650				
ZGK90	157	120	95	86	79	69	62	56	46	90	830	DN300	1500	1100	1580
ZGK110	190	150	115	104	93	85	72	67	57	11	880				
ZGK132	221	170	136	122	108	99	86	79	67	132	930				
ZGK150	252	190	156	140	122	112	9	90	77	150	1450	DN300	1800	1500	2080
ZGK185	314	230	190	171	155	136	124	112	91	185	1720				
ZGK225	380	290	228	208	183	164	145	132	111	225	2140	DN400	2300	1700	2140
ZGK300	504	378	312	276	243	220	198	181	150	300	2320				

When the atmospheric conditions and medium are varied, the relative performance conversion calculation will be different, we can re-designed in accordance with the requirement of users to adapte to different working condition. There are two cooling methods for air suspension centrifugal blower: self-circulating water cooling and forced

air cooling. If you have special requirements on the cooling mode, please tell us in advance.







Scope of application

It is suitable for sewage treatment industry, petrochemical industry, food and drug industry, textile industry, metallurgy industry, cement and construction materials industry, printing and dyeing industry and other industries.

Market Distribution

We have 42 offices throughout the country, in addition to Taiwan Province, 33 provinces in the country's ad-ministrative regions have a sound sales and service network. We can provide you with pre-sale, in-sale and after-sales service in a timely and convenient manner, understand your needs, and constantly improve the service and quality system while meeting the customized needs of customers.

High Performance Aerodynamic Design Methodology for Wide Service Conditions

By studying the influence of impeller and volute flow on efficiency and working stability, the R&D team proposed a flow control method and a pneumatic optimization design method to improve the performance of the main engine, which greatly improved the efficiency of the main engine.


Manufacturing & Equipment Base

has built laboratories, R& D buildings, processing workshops, etc., with internationally advanced and China leading highprecision processing equipment.



High power density permanent magnet synchronous motor technology

Based on the thermal multiphysics coupling design technology of electro magneticmachine, the R&D team independently developed a permanent magnet synchronous motor (PMSM); Through the electromagnetic optimization design technology of high speed permanent magnet motor coordinated with the control strategy, the problems of large rotor heat, high torque ripple and large motor noise are solved, so that it has the advantages of high reliability, high temperature resistance and low wind resistance loss. The design and process of rotor structural integrity were overcome, and a permanent magnet synchronous motor with high power density, low cost and high efficiency was developed.



 $Yixing\ Yicheng\ Street\ Hardware\ Electromechanical\ City,\ Phase\ I,\ Block\ 5,\ District\ 3,\ 8071$

1017 107 2002 100720000@qq.oom