

High-Efficiency and Low Noise Suspension Centrifugal Blower with Foil Bearing Technology for Industrial Applications

Basic Information

Place of Origin: ChinaBrand Name: Aipu

Certification: CE CCC SABS TUV RoHS
Model Number: Air Suspension Blowers

Minimum Order Quantity:

• Price: Negotiable

Packaging Details: Export Standard Packaging

• Payment Terms: T/T, L/C



Product Specification

Flow Range: 5-500m³/min
Boost: 5-120kPa
Temperature: Up To 60°C
Filtration Efficiency: Up To 85 Per Cent

High-Efficiency and Low Noise Suspension Centrifugal Blower with Foil Bearing Technology for Industrial Applications

Product Description

Foil Bearing High-speed Centrifugal Blowers is a high-efh.ciency,energy-saving,green and environmentally friendlyproduct, its mechanical structure is simple, the moving partsare few, the control robustness is good, and the maintenanceis convenient. It adopts automotive-grade oil-free andhigh-reliability dynamic pressure foil bearing, which has nofriction and small mechanical loss during operation. Usingadvanced permanent magnet synchronous motortechnology, the maximum speed can reach 95000rpm, and itonly takes 5s to run at full speed. The motor effciency is ashigh as 97%, which meets the two-stage energy effciencystandard.

The high-effciency ternary flow impeller used in the FoilBearing High-speed Centrifugal Blowers breaks through thekey technology of low specifc speed design and has higheffciency. The integrated special design of the main enginemakes the noise less than 75dB(A) and the vibration less than12um. It adopts stepless adjustment, and the blower can startand stop quickly, and the number of continuous starts andstops exceeds 200,000 times.

Foll Bearing Technology

Foil bearing has physical contact between therotor and the bearing before starting, therelative movement of the rotor and the bearinggenerates air pressure when starting, when therotor rotates, the speed of the air around therotor can be converted into pressure energy, andthe air pressure makes the rotor float when therotor reaches a certain rotation speed and playsa lubricatingrole. Foil bearing technologyeffectively solves the problems of lowefficiency, short life, and the need forregularmaintenance and lubrication of the traditional mechanical support transmission system.



Air Suspension Bearing High Speed Centrifugal Blower Series Selection

Air Flow (spin) dates 000C CF0/ PH, despite 40(sp/sp0 T) large sp															
Air Flow (m/min):1atm,20°C,65%RH, density=12kg/m3, Tolerance=+5%															
model										power	Weight	Outlet calibre Dimension ((mm)	
number	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1	1.2	kw	ka	PN1.0 MPa	oldor	width	height
	Inle	Inlet Flow(m³/min)									kg	FINI.U IVIFA	eidei	widin	rieigrit
ZGK15	24	17	14	13	10	7	/	/	7	15	300	DN150	1300	800	1230
ZGK22	36	29	24	21	18	16	/	/	/	22	310				
ZGK30	49	39	33	28	25	22	/	/	7	30	330				
ZGK37	62	48	41	35	31	28	25	22	19	37	350				
ZGK45	78	62	51	45	31	34	32	28	23	45	550	DN200	1500	1100	1580
ZGK55	94	76	60	54	47	40	38	34	28	55	630				
ZGK75	124	95	76	69	63	55	49	45	37	75	650				
ZGK90	157	120	95	86	79	69	62	56	46	90	830	DN300	1500	1100	1580
ZGK110	190	150	115	104	93	85	72	67	57	11	880				
ZGK132	221	170	136	122	108	99	86	79	67	132	930				
ZGK150	252	190	156	140	122	112	9	90	77	150	1450	DN300	1800	1500	2080
ZGK185	314	230	190	171	155	136	124	112	91	185	1720				
ZGK225	380	290	228	208	183	164	145	132	111	225	2140	DN400	2300	1700	2140
ZGK300	504	378	312	276	243	220	198	181	150	300	2320				

When the atmospheric conditions and medium are varied, the relative performance conversion calculation will be different, we can re-designed in accordance with the requirement of users to adapt to different working condition. There are two cooling methods for air suspension centrifugal blower: self-circulating water cooling and forced air cooling. If you have special requirements on the cooling mode, please tell us in advance.







Scope of application

It is suitable for sewage treatment industry, petrochemical industry, food and drug industry, textile industry, metallurgy industry, cement and construction materials industry, printing and dyeing industry and other industries.

Market Distribution

We have 42 offices throughout the country, in addition to Taiwan Province, 33 provinces in the country's ad-ministrative regions have a sound sales and service network. We can provide you with pre-sale, in-sale and after-sales service in a timely and convenient manner, understand your needs, and constantly improve the service and quality system while meeting the customized needs of customers.

High Performance Aerodynamic Design Methodology for Wide Service Conditions

By studying the influence of impeller and volute flow on efficiency and working stability, the R&D team proposed a flow control method and a pneumatic optimization design method to improve the performance of the main engine, which greatly improved the efficiency of the main engine.


Manufacturing & Equipment Base

has built laboratories, R& D buildings, processing workshops, etc., with internationally advanced and China leading highprecision processing equipment.



High power density permanent magnet synchronous motor technology

Based on the thermal multiphysics coupling design technology of electro magneticmachine, the R&D team independently developed a permanent magnet synchronous motor (PMSM); Through the electromagnetic optimization design technology of high speed permanent magnet motor coordinated with the control strategy, the problems of large rotor heat, high torque ripple and large motor noise are solved, so that it has the advantages of high reliability, high temperature resistance and low wind resistance loss. The design and process of rotor structural integrity were overcome, and a permanent magnet synchronous motor with high power density, low cost and high efficiency was developed.













Yixing Yicheng Street Hardware Electromechanical City, Phase I, Block 5, District 3, 8071