



7.5-132kW Electric Micro Oil Screw Air Compressor 0.65-0.9Mpa

Our Product Introduction

for more products please visit us on aipukqdl.com

Basic Information

- Place of Origin: China
- Brand Name: Aipu
- Model Number: BK/BKX/BMVF/GVT/PVGX
- Minimum Order Quantity: 1PC
- Price: negotiable
- Packaging Details: container
- Delivery Time: 10
- Payment Terms: tt
- Supply Ability: 10000t/y



Product Specification

- Exhaust Pressure: 0.65-0.9Mpa
- Displacement: 01.0-24m³/min
- Type: BMVF Micro Oil Screw Air Compressor
- Power Source: Electric
- Motor Power: 7.5-132kW
- Highlight: **7.5-132kW electric screw air compressor, oil screw air compressor 0.65-0.9Mpa, industrial micro oil air compressor**

Product Description

Product Description:

BMVF air compressor belongs to screw compressor, which uses a pair of interlocking screw rotors to continuously change the volume between teeth during rotation, thereby achieving the suction, compression and discharge of air. Specifically, air enters the compressor through the intake port, is gradually compressed by the screw rotor, increases in pressure, and then discharged from the exhaust port, becoming compressed air with a certain pressure and flow rate, which can meet the needs of various industrial applications..

Core advantages:

Energy saving and efficient: By adopting permanent magnet frequency conversion technology, the motor speed can be automatically adjusted according to changes in gas consumption, and the exhaust volume can be precisely adjusted, enabling the air compressor to maintain high efficiency under any gas consumption conditions, with a comprehensive energy saving of up to 50%.

Wide range adjustment: The adjustment range is 20% -100%. Compared with the 40% -100% adjustment range of ordinary frequency converters, it can still work normally even when deviating from working conditions by 80%, adapting to various complex gas working conditions.

Low noise operation: By optimizing the design and adopting advanced noise reduction technology, the noise during operation is relatively low, such as the BMVF22 model with a noise level of only 40 decibels, creating a quiet working environment for users.

Stable and reliable: With first-class processing and testing equipment such as Mitsui machining centers in Japan, KAPP screw rotor grinders in Germany, and HOLROYD screw rotor grinders in the UK, we ensure high precision and quality of our products, stable operation of the main engine, and long service life.

Compact structure: Adopting a fixed compressor design, the external dimensions are relatively small, the structure is compact, and the footprint is small. For example, the external dimensions of BMVF11 are 1000 × 670 × 1090mm, which is easy to install and place, and can adapt to different working site conditions.

Easy maintenance: The shell design of the air compressor is easy to disassemble and install, the internal component layout is reasonable, and daily maintenance and upkeep operations are simple and convenient, which can reduce the maintenance cost and workload of users.

Product Selection Table:

BK series

Product Model	Exhaust pressure(Mpa)	Exhaust volume(m ³ /min)	Motor power(KW)	Exhaust interface	Weight(kg)	External dimensions(mm)
BK7.5-8G	0.8	1.2	7.5	G3/4	200	800×620×800
BK7.5-8G	0.8	1.1	7.5	G3/4	200	800×620×800
BK11-8G	0.8	1.7	11	G1	280	1000×670×1090
BK15-8G	0.8	2.4	15	G1	280	1000×670×1090
BK15-8	0.8	2.4	15	G1	270	700×670×1250
BK15-10	1.0	2.2	15	G1	270	700×670×1250
BK15-13	1.3	1.7	15	G1	270	700×670×1250
BK22-8G	0.8	3.5	22	G1	390	1200×800×1120
BK22-10G	1.0	3.2	22	G1	390	1200×800×1120
BK22-13G	1.3	2.7	22	G1	390	1200×800×1120
BK30-8G	0.8	5.0	30	G1 1/2	470	1340×850×1280
BK30-10G	1.0	4.4	30	G1 1/2	470	1340×850×1280
BK30-13G	1.3	3.6	30	G1 1/2	470	1340×850×1280
BK37-8G	0.8	6.0	37	G1 1/2	560	1340×850×1280
BK37-10G	1.0	5.4	37	G1 1/2	560	1340×850×1280
BK37-13G	1.3	4.6	37	G1 1/2	560	1340×850×1280
BK45-8G	0.8	7.1	45	G1 1/2	720	1480×1030×1340
BK45-10G	1.0	6.2	45	G1 1/2	720	1480×1030×1340
BK45-13G	1.3	5.6	45	G1 1/2	720	1480×1030×1340
BK55-8G	0.8	10.0	55	G1 1/2	790	1480×1030×1340
BK55-10G	1.0	7.2	55	G1 1/2	790	1480×1030×1340
BK55-13G	1.3	6.2	55	G1 1/2	790	1480×1030×1340
BK75-8G	0.8	13.0	75	G2	1200	1800×1190×1710
BK90-8G	0.8	16.0	90	G2	1240	1800×1190×1710
BK110-8T	0.8	21.0	110	DN65	1630	2100×1230×1730
BK110-8G	0.8	21.0	110	DN65	1680	2100×1230×1730
BK132-8T	0.8	24.0	132	DN65	1670	2100×1230×1730
BK132-8G	0.8	24.0	132	DN65	1750	2100×1230×1730
KS175A-8F	0.8	24.0	132	DN65	1470	1800×1230×1670
KS150-8-II	0.8	22.0	110	DN65	1950	2100×1230×1730
KS175-8-II	0.8	25.0	132	DN65	1990	2100×1230×1730

BKX series

Product Model	Exhaust pressure(Mpa)	Exhaust volume(m ³ /min)	Motor power(KW)	Exhaust interface	Weight(kg)	External dimensions(mm)
BKX7.5-8	0.8	1.2	7.5	G1	470	1310×720×1650
BKX7.5-10	1.0	1.0	7.5	G1	470	1310×720×1650
BKX7.5-13	1.3	0.8	7.5	G1	470	1310×720×1650

BMVF permanent magnet series

Product Model	Exhaust pressure(Mpa)	Exhaust volume(m³/min)	Motor power(KW)	Exhaust interface	Weight(kg)	External dimensions(mm)
BMVF7.5	0.65-0.9	1.00-1.25	7.5	G3/4	170	880×510×800
BMVF11	0.65-0.9	1.50-1.82	11	G1	220	1000×670×1090
BMVF15	0.65-0.9	2.05-2.35	15	G1	250	1000×670×1090
BMVF22	0.65-0.9	2.95-3.95	22	G1	330	1200×800×1120
BMVF37	0.65-0.9	5.05-6.35	37	G1 1/2	500	1340×850×1280
BMVF45	0.65-0.9	6.45-8.2	45	G1 1/2	660	1480×1030×1365
BMVF55	0.65-0.9	8.20-9.85	55	G1 1/2	710	1480×1030×1365
BMVF75	0.65-0.9	10.50-13.10	75	G2	1170	1800×1190×1710
BMVF90	0.65-0.9	12.50-15.50	90	G2	1180	1800×1190×1710
BMVF110	0.65-0.8	22.0	110	DN65	1770	2700×1230×1730
BMVF132	0.65-0.8	24.0	132	DN65	1860	2700×1230×1730

GVT permanent magnet

series

Product Model	Exhaust pressure(Mpa)	Exhaust volume(m³/min)	Motor power(KW)	Exhaust interface	Weight(kg)	External dimensions(mm)
GVT7.5	0.65-0.9	0.95-1.20	7.5	G3/4	170	880×510×800
GVT15	0.65-0.9	2.05-2.35	15	G1	160	820×670×940
GVT22	0.65-0.9	2.95-3.95	22	G1	240	1010×760×1000
GVT37	0.65-0.9	5.05-6.35	37	G1 1/2	360	1190×850×1230
GVT45	0.65-0.9	6.45-8.2	45	G1 1/2	485	1250×970×1200
GVT55	0.65-0.9	8.20-9.85	55	G1 1/2	565	1250×970×1300

BK series miningsafety products

Product Model	Exhaust pressure(Mpa)	Exhaust volume(m³/min)	Motor power(KW)	Exhaust interface	Weight(kg)	External dimensions(mm)
DLGF6/8-37 (B)	0.8	6.0	37	G1 1/2	560	1340×850×1280
DLGF7/8-45 (B)	0.8	7.0	45	G1 1/2	720	1480×1030×1340
DLGF6/8-55 (B)	0.8	8.6	55	G1 1/2	790	1480×1030×1340
DLGF13/8-75 (B)	0.8	13.0	75	G2	1200	1800×1190×1710
DLGF14/8-90 (B)	0.8	14.0	90	G2	1240	1800×1190×1710
DLGF21/8-132 (B)	0.8	21.0	132	DN65	1680	2100×1230×1730
DLGF24/8-160 (B)	0.8	24.0	160	DN65	1750	2100×1230×1730

PVGX twin-screw laser

dedicated unit

Product Model	Exhaust pressure(Mpa)	Exhaust volume(m³/min)	Motor power(KW)	Exhaust interface	Weight(kg)	External dimensions(mm)
PVGX7.5-16	1.6	0.6	7.5	G1 3/4	450	1570×620×1390
PVGX15-16	1.6	1.5	15	G1 3/4	540	1890×660×1550
PVGX22-16	1.6	2.2	22	G1	720	1890×735×1790

Applications:

Industrial manufacturing: widely used in industries such as mechanical processing, automotive manufacturing, and electronic equipment manufacturing, providing power for various pneumatic tools and production line equipment.

Mining: In mining, it can be used to drive equipment such as rock drills and pickaxes for ore mining and tunnel excavation.

Construction: Suitable for concrete mixing, spraying, door and window installation and other operations in construction, providing compressed air for construction equipment.

Medical and health: In hospitals, clinics and other medical and health institutions, it can be used to drive dental equipment, ventilators and other medical devices to ensure the normal operation of medical work.

Transportation: It can be used in transportation fields such as car maintenance and tire inflation, providing convenience for vehicle maintenance and repair.

Support and Services:

Our Micro oil screw air compressor product comes with comprehensive technical support and services to ensure that our customers are satisfied with their purchase. Our team of experts is available to provide assistance with installation, operation, and maintenance of the product. We also offer repair and replacement services for any faulty parts or components. Additionally, we provide training and educational resources to help our customers maximize the performance and lifespan of their Micro oil screw air compressor.

Packing and Shipping:

Product Packaging:

The Micro oil screw air compressor comes in a sturdy cardboard box with the product image and specifications printed on the outside. Inside, the product is securely packaged with foam inserts to prevent any damage during transportation.

Shipping:

We provide transportation services for micro oil screw air compressors worldwide. Our standard shipping time is 3-5 business days. For expedited shipping, please contact our customer service team. We ship via trusted carriers such as UPS, FedEx, and USPS and provide a tracking number for your convenience.

FAQ:

Q: What is the brand name of this product?

A: The brand name of this product is Aipu.

Q: What is the model number of this product?

A: The model number of this product is Micro oil screw air compressor.

Q: Where is this product made?

A: This product is made in China.

Q: Does this product have any certifications?

A: Yes, this product is certified by ce.ul.

Q: What is the minimum order quantity for this product?

A: The minimum order quantity for this product is 1pc.

Q: Is the price of this product negotiable?

A: Yes, the price of this product is negotiable.

Q: What is the packaging details for this product?
A: The packaging details for this product is container.
Q: How long is the delivery time for this product?
A: The delivery time for this product is 10 days.
Q: What are the payment terms for this product?
A: The payment terms for this product is tt.
Q: What is the supply ability of this product?
A: The supply ability of this product is 10000t/y.



Yixing Aipu Air System Equipment Co., Ltd



13771572002



183426306@qq.com



aipukqdl.com

Yixing Yicheng Street Hardware Electromechanical City, Phase I, Block 5, District 3, 8071