



Yixing Aipu Air System Equipment Co., Ltd

aipukqdl.com



## Efficient and energy-saving micro oil screw air compressor

Our Product Introduction

for more products please visit us on [aipukqdl.com](http://aipukqdl.com)

### Basic Information

- Place of Origin: China
- Brand Name: Aipu
- Model Number: BK/BKX/BMVF/GVT/PVGX
- Minimum Order Quantity: 1PC
- Price: negotiable
- Packaging Details: container
- Delivery Time: 10
- Payment Terms: tt
- Supply Ability: 10000t/y



### Product Specification

- Exhaust Pressure: 0.8-1.6Mpa
- Displacement: 0.6-25m³/min
- Type: BK Micro Oil Screw Air Compressor
- Power Source: Electric
- Motor Power: 7.5-132kW
- Highlight: **energy-saving micro oil air compressor, screw air compressor with warranty, efficient oil screw compressor**

## Product Description

### Product Description:

The BK series is a high-performance and highly reliable micro oil screw air compressor. It is designed to meet the needs of medium and large industrial users for stable, efficient, and clean compressed air. This series of products integrates advanced screw host technology, intelligent control systems, and efficient integrated design, aiming to provide users with the lowest total cost of ownership (TCO). It is an ideal power source for modern factories, manufacturing, energy, chemical and other fields.

### Core advantages:

#### Excellent efficiency and energy saving

Efficient host: Adopting a new generation of asymmetric profile screw rotors, the profile has been optimized for high volumetric efficiency and lower energy consumption.

High quality motor: equipped with high-efficiency energy-saving (IE3/IE4 level) motor, high power factor, smooth start-up, and reliable operation.

Intelligent control system: Built in intelligent controller that can automatically adjust the exhaust volume according to actual gas demand (such as loading and unloading, capacity adjustment or frequency conversion control), avoiding unnecessary energy waste.

#### Excellent reliability and durability

Heavy duty design: Key components such as the main engine, oil and gas tank, and cooler are all reinforced to ensure long-term stable operation of the equipment under harsh working conditions.

Top grade bearings and seals: Using internationally renowned brand bearings and high-quality seals greatly extends the service life of the host and the entire machine.

Excellent cooling system: large-sized plate fin cooler, optimized air duct design to ensure low operating temperature even in high temperature environments and prevent performance degradation.

#### High quality air output

Micro oil technology: Excellent oil and gas separation system, using multi-stage separation (mechanical centrifugation+high-efficiency oil and gas separation filter element), with extremely low oil content in the outlet air (can stably reach  $\leq 3$ ppm, some models are even higher), providing cleaner compressed air and protecting backend gas equipment.

Built in energy-saving air filter: designed with low intake resistance and large dust holding capacity, it can effectively protect the host from dust erosion.

#### Intelligent control and humanized operation

Intelligent controller: Large screen color touch screen (or Chinese LCD display), real-time monitoring of all key parameters such as pressure, temperature, operating status, maintenance reminders, etc.

Remote monitoring: Supports communication interfaces such as RS485, Modbus, Ethernet, etc., making it easy to connect to factory Internet of Things (IIoT) systems for remote monitoring, data collection, and centralized management.

Fault diagnosis and protection: It has multiple safety protection functions (such as overload, overtemperature, overpressure, phase loss), and can automatically record fault information for easy and quick troubleshooting.

#### Convenient maintainability

One stop maintenance point: Daily maintenance components such as oil filters, air filters, and oil separation cores are centrally arranged, and can be accessed by opening the door (or side panel), making replacement easy and fast, reducing downtime.

Low maintenance cost: The long-life design and high-quality consumables extend maintenance intervals, effectively reducing long-term maintenance costs.

### Product Selection Table:

BK series

| Product Model | Exhaust pressure(Mpa) | Exhaust volume(m³/min) | Motor power(KW) | Exhaust interface | Weight(kg) | External dimensions(mm) |
|---------------|-----------------------|------------------------|-----------------|-------------------|------------|-------------------------|
| BK7.5-8G      | 0.8                   | 1.2                    | 7.5             | G3/4              | 200        | 800×620×800             |
| BK7.5-9G      | 0.8                   | 1.1                    | 7.5             | G3/4              | 200        | 800×620×800             |
| BK11-8G       | 0.8                   | 1.7                    | 11              | G1                | 280        | 1000×670×1090           |
| BK15-8G       | 0.8                   | 2.4                    | 15              | G1                | 280        | 1000×670×1090           |
| BK15-8        | 0.8                   | 2.4                    | 15              | G1                | 270        | 700×670×1250            |
| BK15-10       | 1.0                   | 2.2                    | 15              | G1                | 270        | 700×670×1250            |
| BK15-13       | 1.3                   | 1.7                    | 15              | G1                | 270        | 700×670×1250            |
| BK22-8G       | 0.8                   | 3.5                    | 22              | G1                | 390        | 1200×800×1120           |
| BK22-10G      | 1.0                   | 3.2                    | 22              | G1                | 390        | 1200×800×1120           |
| BK22-13G      | 1.3                   | 2.7                    | 22              | G1                | 390        | 1200×800×1120           |
| BK30-8G       | 0.8                   | 5.0                    | 30              | G1 1/2            | 470        | 1340×850×1280           |
| BK30-10G      | 1.0                   | 4.4                    | 30              | G1 1/2            | 470        | 1340×850×1280           |
| BK30-13G      | 1.3                   | 3.6                    | 30              | G1 1/2            | 470        | 1340×850×1280           |
| BK37-8G       | 0.8                   | 6.0                    | 37              | G1 1/2            | 560        | 1340×850×1280           |
| BK37-10G      | 1.0                   | 5.4                    | 37              | G1 1/2            | 560        | 1340×850×1280           |
| BK37-13G      | 1.3                   | 4.6                    | 37              | G1 1/2            | 560        | 1340×850×1280           |
| BK45-8G       | 0.8                   | 7.1                    | 45              | G1 1/2            | 720        | 1480×1030×1340          |
| BK45-10G      | 1.0                   | 6.2                    | 45              | G1 1/2            | 720        | 1480×1030×1340          |
| BK45-13G      | 1.3                   | 5.6                    | 45              | G1 1/2            | 720        | 1480×1030×1340          |
| BK55-8G       | 0.8                   | 10.0                   | 55              | G1 1/2            | 790        | 1480×1030×1340          |
| BK55-10G      | 1.0                   | 7.2                    | 55              | G1 1/2            | 790        | 1480×1030×1340          |
| BK55-13G      | 1.3                   | 6.2                    | 55              | G1 1/2            | 790        | 1480×1030×1340          |
| BK75-8G       | 0.8                   | 13.0                   | 75              | G2                | 1200       | 1800×1190×1710          |
| BK90-8G       | 0.8                   | 16.0                   | 90              | G2                | 1240       | 1800×1190×1710          |
| BK110-8T      | 0.8                   | 21.0                   | 110             | DN65              | 1630       | 2100×1230×1730          |
| BK110-8G      | 0.8                   | 21.0                   | 110             | DN65              | 1680       | 2100×1230×1730          |
| BK132-8T      | 0.8                   | 24.0                   | 132             | DN65              | 1670       | 2100×1230×1730          |
| BK132-8G      | 0.8                   | 24.0                   | 132             | DN65              | 1750       | 2100×1230×1730          |
| KS175A-8F     | 0.8                   | 24.0                   | 132             | DN65              | 1470       | 1800×1230×1670          |
| KS150-8-II    | 0.8                   | 22.0                   | 110             | DN65              | 1950       | 2100×1230×1730          |
| KS175-8-II    | 0.8                   | 25.0                   | 132             | DN65              | 1990       | 2100×1230×1730          |

BKX series

| Product Model | Exhaust pressure(Mpa) | Exhaust volume(m³/min) | Motor power(KW) | Exhaust interface | Weight(kg) | External dimensions(mm) |
|---------------|-----------------------|------------------------|-----------------|-------------------|------------|-------------------------|
| BKX7.5-8      | 0.8                   | 1.2                    | 7.5             | G1                | 470        | 1310×720×1650           |
| BKX7.5-10     | 1.0                   | 1.0                    | 7.5             | G1                | 470        | 1310×720×1650           |
| BKX7.5-13     | 1.3                   | 0.8                    | 7.5             | G1                | 470        | 1310×720×1650           |

BMVF permanent magnet

series

| Product Model | Exhaust pressure(Mpa) | Exhaust volume(m³/min) | Motor power(KW) | Exhaust interface | Weight(kg) | External dimensions(mm) |
|---------------|-----------------------|------------------------|-----------------|-------------------|------------|-------------------------|
| BMVF7.5       | 0.65-0.9              | 1.00-1.25              | 7.5             | G3/4              | 170        | 880×510×800             |
| BMVF11        | 0.65-0.9              | 1.50-1.82              | 11              | G1                | 220        | 1000×670×1090           |
| BMVF15        | 0.65-0.9              | 2.05-2.35              | 15              | G1                | 250        | 1000×670×1090           |
| BMVF22        | 0.65-0.9              | 2.95-3.95              | 22              | G1                | 330        | 1200×800×1120           |
| BMVF37        | 0.65-0.9              | 5.05-6.35              | 37              | G1 1/2            | 500        | 1340×850×1280           |
| BMVF45        | 0.65-0.9              | 6.45-8.2               | 45              | G1 1/2            | 660        | 1480×1030×1365          |
| BMVF55        | 0.65-0.9              | 8.20-9.85              | 55              | G1 1/2            | 710        | 1480×1030×1365          |
| BMVF75        | 0.65-0.9              | 10.50-13.10            | 75              | G2                | 1170       | 1800×1190×1710          |
| BMVF90        | 0.65-0.9              | 12.50-15.50            | 90              | G2                | 1180       | 1800×1190×1710          |
| BMVF110       | 0.65-0.8              | 22.0                   | 110             | DN65              | 1770       | 2700×1230×1730          |
| BMVF132       | 0.65-0.8              | 24.0                   | 132             | DN65              | 1860       | 2700×1230×1730          |

GVT permanent magnet

series

| Product Model | Exhaust pressure(Mpa) | Exhaust volume(m³/min) | Motor power(KW) | Exhaust interface | Weight(kg) | External dimensions(mm) |
|---------------|-----------------------|------------------------|-----------------|-------------------|------------|-------------------------|
| GVT7.5        | 0.65-0.9              | 0.95-1.20              | 7.5             | G3/4              | 170        | 880×510×800             |
| GVT15         | 0.65-0.9              | 2.05-2.35              | 15              | G1                | 160        | 820×670×940             |
| GVT22         | 0.65-0.9              | 2.95-3.95              | 22              | G1                | 240        | 1010×760×1000           |
| GVT37         | 0.65-0.9              | 5.05-6.35              | 37              | G1 1/2            | 360        | 1190×850×1230           |
| GVT45         | 0.65-0.9              | 6.45-8.2               | 45              | G1 1/2            | 485        | 1250×970×1300           |
| GVT55         | 0.65-0.9              | 8.20-9.85              | 55              | G1 1/2            | 565        | 1250×970×1300           |

BK series miningsafety products

| Product Model    | Exhaust pressure(Mpa) | Exhaust volume(m³/min) | Motor power(KW) | Exhaust interface | Weight(kg) | External dimensions(mm) |
|------------------|-----------------------|------------------------|-----------------|-------------------|------------|-------------------------|
| DLGF6/8-37 (B)   | 0.8                   | 6.0                    | 37              | G1 1/2            | 560        | 1340×850×1280           |
| DLGF7/8-45 (B)   | 0.8                   | 7.0                    | 45              | G1 1/2            | 720        | 1480×1030×1340          |
| DLGF8/8-55 (B)   | 0.8                   | 9.6                    | 55              | G1 1/2            | 790        | 1480×1030×1340          |
| DLGF13/8-75 (B)  | 0.8                   | 13.0                   | 75              | G2                | 1200       | 1800×1190×1710          |
| DLGF14/8-90 (B)  | 0.8                   | 14.0                   | 90              | G2                | 1240       | 1800×1190×1730          |
| DLGF21/8-132 (B) | 0.8                   | 21.0                   | 132             | DN65              | 1680       | 2100×1230×1730          |
| DLGF24/8-160 (B) | 0.8                   | 24.0                   | 160             | DN65              | 1750       | 2100×1230×1730          |

PVGX twin-screw laser

dedicated unit

| Product Model | Exhaust pressure(Mpa) | Exhaust volume(m³/min) | Motor power(KW) | Exhaust interface | Weight(kg) | External dimensions(mm) |
|---------------|-----------------------|------------------------|-----------------|-------------------|------------|-------------------------|
| PVGX7.5-16    | 1.6                   | 0.6                    | 7.5             | G1 3/4            | 450        | 1570×620×1390           |
| PVGX15-16     | 1.6                   | 1.5                    | 15              | G1 3/4            | 540        | 1890×660×1550           |
| PVGX22-16     | 1.6                   | 2.2                    | 22              | G1                | 720        | 1890×735×1790           |

## Applications:

Manufacturing industry: automobile manufacturing, electronic appliances, hardware processing, textile and chemical fiber

Energy and Chemical Industry: Mining, Power Plants, Petrochemical, Fertilizer Production

Infrastructure construction: Bridge and tunnel construction, building materials production (cement, glass)

Food and medicine: (requiring backend purification equipment) Beverage filling, pharmaceutical manufacturing

Other: Any industrial scenario that requires a large amount of stable and clean compressed air

## Support and Services:

Our Micro oil screw air compressor product comes with comprehensive technical support and services to ensure that our customers are satisfied with their purchase. Our team of experts is available to provide assistance with installation, operation, and maintenance of the product. We also offer repair and replacement services for any faulty parts or components. Additionally, we provide training and educational resources to help our customers maximize the performance and lifespan of their Micro oil screw air compressor.

## Packing and Shipping:

**Product Packaging:**

The Micro oil screw air compressor comes in a sturdy cardboard box with the product image and specifications printed on the outside. Inside, the product is securely packaged with foam inserts to prevent any damage during transportation.

**Shipping:**

We provide transportation services for micro oil screw air compressors worldwide. Our standard shipping time is 3-5 business days. For expedited shipping, please contact our customer service team. We ship via trusted carriers such as UPS, FedEx, and USPS and provide a tracking number for your convenience.

**FAQ:**

**Q: What is the brand name of this product?**

A: The brand name of this product is Aipu.

**Q: What is the model number of this product?**

A: The model number of this product is Micro oil screw air compressor.

**Q: Where is this product made?**

A: This product is made in China.

**Q: Does this product have any certifications?**

A: Yes, this product is certified by ce.ul.

**Q: What is the minimum order quantity for this product?**

A: The minimum order quantity for this product is 1pc.

**Q: Is the price of this product negotiable?**

A: Yes, the price of this product is negotiable.

**Q: What is the packaging details for this product?**

A: The packaging details for this product is container.

**Q: How long is the delivery time for this product?**

A: The delivery time for this product is 10 days.

**Q: What are the payment terms for this product?**

A: The payment terms for this product is tt.

**Q: What is the supply ability of this product?**

A: The supply ability of this product is 10000t/y.



**Yixing Aipu Air System Equipment Co., Ltd**



13771572002



183426306@qq.com



aipukqdl.com

Yixing Yicheng Street Hardware Electromechanical City, Phase I, Block 5, District 3, 8071